



ELECTRICAL

Matching Impedance: 75 unbalanced coaxial to 120 balanced twisted pair
 Bit Rates: From 2Mbit/s up to 45Mbit/s as ITU-T Recommendation G.703 Line Code
 Return Loss: >10dB in the frequency range of 51~102kHz
 >15dB in the frequency range of 1~70MHz
 Insertion Loss: <0.5dB @ 1MHz; <0.4dB @ 4MHz; <0.6dB @ 17MHz
 <0.9dB in the range of 0.2~70MHz
 Cross Talk: >60dB in the range of 1.0~70MHz between 2 baluns mounted on DDF strip
 Pulse Shape: 2Mbit/s, 8Mbit/s, 34MHz and 45MHz as per G.703
 Signal Levels: 2.37V nominal peak voltage for 2Mbit/s and 8Mbit/s at the coaxial end as per G.703
 1V nominal peak voltage for 34Mbit/s at the coaxial end as per G.703
 45Mbit/s conforms to its interface pulse mask in G.703

MATERIALS

Coax Connector Outer Contact:	Brass Alloy AS 1567 Type 385. Finish Cu/Ni
Coax Connector Body:	Brass Alloy AS 1567 Type 385. Finish Cu/Ni
Coax Connector Insulator:	PTFE
Coax Connector Inner Contact:	Phosphor Bronze. Finish Cu/Ni/Au
Balun Body:	Brass Alloy AS 1567 Type 385. Finish Cu/Ni/Sn
Outer Sleeve and Base Moulding:	Noryl Black
IDC Moulding:	Polycarbonate White

COAXIAL CONNECTOR (75)

BNC Series: To IEC 169-8
 Mating Cycles: 500

IDC CONTACTS

Wire Size: 0.4mm to 0.65mm conductor diameter
 Insulation diameter 0.7mm to 1.4mm
 Finish: Tin plated
 Mating Cycles: 50

ENVIRONMENTAL

Working Temperature: -10°C to 75°C
 RoHS Compliance: To EU Directive 2011/65/EU

TERMINATION

IDC Termination: Krone Terminating Tool

