



PRODUCT DESCRIPTION

This Balun Panel converts E1 and E2 G.703 signals from unbalanced 75 coaxial to balanced 120 twisted pair transmissions. A bi-directional device requiring no external power, it allows the user to connect telecommunications equipment with mismatched interfaces. This product offers the following features:-

- coax to twisted pair conversion
- 75 to 120 impedances
- mounts in standard 19" rack
- zinc sealed, powder coated steel
- exceeds G.703 requirements
- 1.6/5.6(f) to MDR68(f) (Mini Centronics)
- >33dB return loss 0.3 to 3MHz
- mount recessed to ease cable entry
- gold plated contacts
- ETSI and 23" brackets available
- RoHS compliant
- <0.15dB E1 insertion loss
- mount coax or MDR68 to front
- teflon coaxial insulators
- optional designation strips

OPERATING CONDITIONS

Matching Impedance: 75 unbalanced coaxial to 120 balanced twisted pair
 Bit Rate: 2Mbit/s (E1) and 8Mbit/s (E2) per ITU-T G.703 Line Code
 Signal Level: 2.37V nominal peak voltage at the coaxial end per G.703
 Working Temperature: -30°C to 75°C

ELECTRICAL SPECIFICATIONS

Insertion Loss: <0.15dB from 51kHz to 3.072MHz (2Mbit/s, E1) and <0.20dB from 211kHz to 12.672MHz (8Mbit/s, E2) in both directions
 Return Loss: Exceeds G.703 by >13dB for 2Mbit/s and >8dB for 8Mbit/s
 Pulse Shape: Exceeds G.703 requirements for 2Mbit/s and 8Mbit/s
 Cross Talk: >65dB from 51kHz to 12.672MHz between channels (>50dB for adjacent MDR68 connector contacts)
 Isolation Voltage: >250V DC

MECHANICAL SPECIFICATIONS

Coaxial Connector: 1.6/5.6 female to IEC 169-13
 Body: Brass, Plated Cu/Ni/Au
 Pin: Beryllium Copper, Plated Cu/Ni/Au
 Insulator: Teflon
 Mating Cycles: 500min
 MDR68 Connector (SCSI): Contacts: Phosphor Bronze, Plated Ni/Au
 Moulding: Thermoplastic, Black
 Shell: Steel, Plated Ni
 Housing: Die Cast, Plated Ni
 Panel: Steel, Zinc Sealed and Powder Coated Black
 Panel Insulators: Thermoplastic, Black

ACCESSORIES

Cable Assemblies: MDR68(m) to MDR68(m) on shielded 34 pair cable
 Mounting Brackets: For ETSI 21" and 23" racks
 Cable Management Kits: For 19", 21" and 23" racks

