

PRODUCT DESCRIPTION

This rack mounting Balun Panel converts 16 G.703 E1 or E2 transmissions from unbalanced 75Ω coaxial to balanced 120Ω twisted pair. A bi-directional device requiring no external power, it connects telecommunications equipment with mismatched interfaces or facilitates the conversion from coaxial to twisted pair distribution wiring. In addition this product offers the following features:-


- coax to twisted pair conversion
- exceeds G.703 requirements
- >33dB return loss 0.3 to 3MHz
- shielded construction
- Krone style IDC
- BNC(f) connector to IEC 169-8
- 75Ω to 120Ω impedances
- <0.16dB E1 insertion loss
- gold plated pin
- long life & high reliability
- 2 and 8Mbit/s data rates
- RoHS compliant
- >80dB cross talk
- teflon coaxial insulators
- uses AC&E B13019010 balun

OPERATING CONDITIONS

Matching Impedance: 75ohm unbalanced coaxial to 120ohm balanced twisted pair
 Bit Rate: 2Mbit/s (E1) and 8Mbit/s (E2) per ITU-T G.703 Line Code
 Signal Level: 2.37V nominal peak voltage at the coaxial end per G.703
 Working Temperature: -30°C to 75°C

ELECTRICAL SPECIFICATIONS

Insertion Loss: <0.16dB from 51kHz to 3.072MHz (E1) and <0.3dB from 211kHz to 12.672MHz (E2) in both directions
 Return Loss: 2Mbit/s exceeds G.703 requirements (>25dB from 51kHz to 3.072MHz) 8Mbit/s as per G.703 requirements
 Pulse Shape: Exceeds G.703 requirements for 2Mbit/s and 8Mbit/s
 Cross Talk: >80dB from 51kHz to 12.672MHz
 Isolation Voltage: Coax to Twisted Pair >250V DC



MECHANICAL SPECIFICATIONS

Coaxial Connector: BNC female to IEC 169-8
 Body: Brass, Plated Nickel
 Pin: Phosphor Bronze, Plated Gold
 Insulator: Teflon
 Mating Cycles: 500min
 IDC Connector: Wire: Conductor Ø0.4 to 0.65mm, Insulation Ø0.7 to 1.4mm
 Contacts: Tin Plated
 Moulding: Thermoplastic White
 Mating Cycles: 50min
 Mouldings: Noryl Black
 Panel: Steel, Zinc Sealed and Powder Coated Black

TERMINATION

IDC: Krone Connection Tool 6089 2 003-00 or 6417 1 810-02